

NIGHTTRIDE

== THERMAL ==


PRO-SL



OWN THE NIGHT

NIGHTRIDE

PRO-SL



TECHNICAL SPECIFICATIONS

Spotlight Mount	UNITY S04	UNITY S04
Sealed Design	IP67	IP67
Power Consumption	4W max	4W max
Power Requirement	12-16 VDC	12-16 VDC
Operating Temperature	-40°F - +140°F	-40°F - +140°F
Lens	13MM	13MM
Resolution	384 X 288 uncooled microbolometer	640 X 512 uncooled microbolometer
Lens Heater	Yes	Yes
Field of View	28° (H)	28° (H)
Frames Per Sec	25hz	25hz
Sensor Pixel Size	17 micron	12 micron
Color Palettes	black, white, green, rainbow	black, white, green, rainbow
Visibility	480 yards	660 yards
Digital Zoom	1x, 2x, 4x, 8x	1x, 2x, 4x, 8x
Object Focus Range	20 feet to infinity	20 feet to infinity

PRO-SL- FULL SITUATIONAL AWARENESS

WHAT SETS IT APART:

NightRide Pro-SL provides a distinct and discreet advantage - sensing heat signatures greater than quarter-mile down the road through dust, smoke, rain, snow or fog. Whether engaging in enforcement, search and rescue, firefighting, or emergency management, NightRide Pro-SL provides critical seconds to prepare and react in any situation.

FEATURES:

- Unity S04 Spotlight Mount
- Unity S14 Spotlight may be modified to accommodate camera
- WiFi hotspot connection to display
- mechanical pan/tilt
- Always recording/event recording

